

Application instructions and technical oveview

Pro-410™ is a high quality, solvent based surface sealer based on acrylic resins. It is an impregnating and non-degrading sealer that has a **MATT finish** and enhances the colour of natural stone and concrete paving. It is used for impregnation, sealing and binding of natural stone, concrete, screeds, block paving, brickwork and masonry, particularly in aggressive environments. Seals and protects surfaces from water penetration, staiing and the effects of natural weathering whilst remaining breathable. Will also provide an effective anti-carbonation coating to concrete.

Pro-410[™] can also be used to bind and stabilise block paving joint sand.

preparation

Substrates should be sound, clean and free from dirt, dust, oil, etc and must be totally dry. We recommend cleaning with Nexus Paving & Driveway Cleaner prior to application.

As with all sealants, always try a small inconspicuous test area before full application.

application

Pro-410™ Paving Sealer is supplied ready for use and should be applied when the surface temperature is between 5°C and 30°C. Application may be made by brush, roller or spray. Apply a complete, even coat over the whole surface - ensuring any excess is removed. One coat will provide a matt finish and is usually sufficient for most applications, however we recommend a second coat for increased protetion and colour enhancement. For anti-carbonation coating, two coats should be applied - the second coat being applied 6-8 hours after the first.

Protect from rain until cured - dryness will normally occur within 2 hours with full curing taking up to 24hours.

We recommend using white spirit to clean brushes and/or rollers.



coverage

Pro-410™ covers approximately 4.5 to 7m² per litre per coat, depending on substrate porosity.

Order code:	Item Description:	Colour:	Pack Size:	Pallet Qty:
PRO4101	Pro-410™ Paving Sealer	Matt, enhancer	1 litre	box qty: 12
PRO4105	Pro-410™ Paving Sealer	Matt, enhancer	5 litres	160
PRO41025	Pro-410™ Paving Sealer	Matt, enhancer	25 litres	24